

Goshute Canyon Wilderness

Legal Boundary Description

The boundary of the Goshute Canyon Wilderness established in the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006, Bureau of Land Management serial No. N-83921, located in Townships 24 North, Ranges 62 and 63 East, Townships 25 North, Ranges 62, 63, and 64 East and Townships 26 North, Ranges 63 and 64 East, Mount Diablo Meridian, White Pine County, in the state of Nevada, is more particularly described as follows:

1. BEGINNING at the corner of sections 17, 18, 19, and 20, T. 26 N., R. 63 E.; thence easterly, a distance of approximately 0.9 miles, on the line between sections 17 and 20 to intersection with a line parallel with and 100 feet westerly of the westerly edge of an unimproved road, bears northerly and southerly, at approximate latitude 40°07'19" North, longitude 114°53'07" West;
2. thence southerly, a distance of approximately 1.8 miles, on a line parallel with and 100 feet westerly of the westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°05'54.312" North, longitude 114°52'45.635" West;
3. thence N. 85°08'30" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of the unimproved road, at observed latitude 40°05'54.487" North, longitude 114°52'42.944" West;
4. thence northerly, a distance of approximately 0.1 mile, to the center-west, one-sixteenth section corner of section 28, T. 26 N., R. 63 E.;
5. thence easterly, a distance of approximately 0.25 miles, on the east and west center line of section 28, T. 26 N., R. 63 E., to the center one-quarter section corner of section 28;
6. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of section 28, T. 26 N., R. 63 E., to the one-quarter section corner of sections 21 and 28;
7. thence westerly, a distance of approximately 0.25 miles, on the line between sections 21 and 28, T. 26 N., R. 63 E., to the west one-sixteenth section corner of sections 21 and 28, T. 26 N., R. 63 E.;
8. thence westerly, a distance of approximately 0.2 miles, on the line between sections 21 and 28, T. 26 N., R. 63 E., to intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in

- course No. 2, bears northerly and southerly, at approximate latitude 40°06'27" North, longitude 114°53'00" West;
9. thence northerly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet easterly of the easterly edge of the unimproved road to intersection with the line between sections 17 and 20, T. 26 N., R. 63 E., at approximate latitude 40°07'19" North, longitude 114°53'04" West;
 10. thence easterly, a distance of approximately 4.0 miles, on the lines between sections 17 and 20, sections 16 and 21, sections 15 and 22, sections 14 and 23, and sections 13 and 24, T. 26 N., R. 63 E., to intersection with a line parallel with and 100 feet easterly of the easterly edge of a jeep trail, at approximate latitude 40°07'16" North, longitude 114°48'35" West;
 11. thence southwesterly, a distance of approximately 1.4 miles, on a line parallel with and northwesterly of the northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°06'36.473" North, longitude 114°49'40.239" West;
 12. thence southerly, a distance of approximately 250 feet, to the base of right bank of a wash, course easterly, at approximate latitude 40°06'34" North, longitude 114°49'40" West;
 13. thence easterly, a distance of approximately 0.3 miles, with the meanders of the base of right bank of a wash, course easterly, to intersection with the north and south center line of the southwest one-quarter of section 24, T. 26 N., R. 63 E., at approximate latitude 40°06'33" North, longitude 114°49'21" West;
 14. thence southerly, a distance of approximately 0.2 miles, on the north and south center line of the southwest one-quarter of section 24, T. 26 N., R. 63 E., to the west one-sixteenth section corner of sections 24 and 25;
 15. thence southerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 25, T. 26 N., R. 63 E., to the northwest one-sixteenth section corner of section 25;
 16. thence easterly, a distance of approximately 0.25 miles, on the east and west center line of the northwest one-quarter of section 25, T. 26 N., R. 63 E., to the center-north, one-sixteenth section corner of section 25;
 17. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of section 25, T. 26 N., R. 63 E., to the one-quarter section corner of sections 24 and 25;
 18. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of section 24, T. 26 N., R. 63 E., to the center-south, one-sixteenth section corner of section 24;

19. thence northerly, a distance of approximately 100 feet, on the north and south center line of section 24, T. 26 N., R. 63 E., to the base of left bank of a wash, course southeasterly, at approximate latitude $40^{\circ}06'38''$ North, longitude $114^{\circ}49'04''$ West;
20. thence northwesterly, a distance of approximately 0.35 miles, with the meanders of the base of left bank of wash, course southeasterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned jeep trail, described in course No. 11, bears northeasterly and southwesterly, at observed latitude $40^{\circ}06'50.742''$ North, longitude $114^{\circ}49'16.441''$ West;
21. thence northeasterly, a distance of approximately 1.0 mile, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the jeep trail to intersection with the line between sections 18 and 19, T. 26 N., R. 64 E., at approximate latitude $40^{\circ}07'16''$ North, longitude $114^{\circ}48'28''$ West;
22. thence easterly, a distance of approximately 1.6 miles, on the lines between sections 18 and 19 and sections 17 and 20, T. 26 N., R. 64 E., to intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of an unimproved road, bears northwesterly and southeasterly, at approximate latitude $40^{\circ}07'15''$ North, longitude $114^{\circ}46'39''$ West;
23. thence southeasterly, a distance of approximately 0.25 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to intersection with a line parallel with and 100 feet northerly of a jeep trail, at approximate latitude $40^{\circ}07'03''$ North, longitude $114^{\circ}46'33''$ West;
24. thence westerly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet northerly of the northerly edge of the jeep trail to intersection with a line parallel with and 100 feet northerly of the northerly edge of a second unimproved road, bears easterly and westerly, at approximate latitude $40^{\circ}07'03''$ North, longitude $114^{\circ}46'46''$ West;
25. thence westerly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to intersection with the north and south center line of the northwest one-quarter of section 20, T. 26 N., R. 64 E., at approximate latitude $40^{\circ}07'04''$ North, longitude $114^{\circ}47'05''$ West;
26. thence southerly, a distance of approximately 150 feet, to the northwest one-sixteenth section corner of section 20, T. 26 N., R. 64 E.;
27. thence southerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 20, T. 26 N., R. 64 E., to the center-west, one-sixteenth

- section corner of section 20;
28. thence easterly, a distance of approximately 0.25 miles, on the east and west center line of section 20, T. 26 N., R. 64 E., to the center one-quarter section corner of section 20;
 29. thence southerly, on the north and south center line of section 20, T. 26 N., R. 64 E., a distance of approximately 0.2 miles, to a point on said line, at approximate latitude $40^{\circ}06'40.1''$ North, longitude $114^{\circ}46'47''$ West;
 30. thence northeasterly, a distance of approximately 400 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, extending easterly, at observed latitude $40^{\circ}06'41.771''$ North, longitude $114^{\circ}46'42.333''$ West;
 31. thence easterly turning southeasterly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet southerly and southwesterly of the southerly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second unimproved road, bears northeasterly and southwesterly, at observed latitude $40^{\circ}05'59.233''$ North, longitude $114^{\circ}45'48.118''$ West;
 32. thence southwesterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 25 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a jeep trail, bears northwesterly and southeasterly, at observed latitude $40^{\circ}05'42.168''$ North, longitude $114^{\circ}46'04.912''$ West;
 33. thence northwesterly turning northerly and westerly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet northeasterly, easterly, and northerly of the northeasterly, easterly, and northerly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude $40^{\circ}06'05.935''$ North, longitude $114^{\circ}46'19.936''$ West;
 34. thence S. $13^{\circ}43'20''$ W., a distance of 210.0 feet, at intersection with a line parallel with and 100 feet southerly of the southerly edge of the jeep trail, to a stainless steel post, 28 inches

- long, 2 1/2 inches diameter, set 18 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 40°06'03.919" North, longitude 114°46'20.577" West;
35. thence easterly turning southerly and southeasterly, a distance of approximately 0.7 miles, on a line parallel with and 100 feet southerly, westerly, and southwesterly of the southerly, westerly, and southwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of aforementioned unimproved road, described in course No. 33, bears northerly and southeasterly, at observed latitude 40°05'37.475" North, longitude 114°46'04.323" West;
 36. thence southeasterly, a distance of approximately 0.45 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to intersection with the north and south center line of the northwest one-quarter of section 33, T. 26 N., R. 64 E., at approximate latitude 40°05'16" North, longitude 114°45'54" West;
 37. thence southerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 33, T. 26 N., R. 64 E., to the center-west, one-sixteenth section corner of section 33;
 38. thence easterly, a distance of approximately 200 feet, on the east and west center line of section 33, T. 26 N., R. 64 E., to intersection with a line parallel with and 100 feet westerly of the westerly edge of an improved road, bears northerly and southerly, at approximate latitude 40°05'03" North, longitude 114°45'51" West;
 39. thence southerly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet westerly of the westerly edge of the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°04'38.670" North, longitude 114°45'50.252" West;
 40. thence westerly, a distance of approximately 500 feet, to a point, at approximate latitude 40°04'38.83" North, longitude 114°45'56.95" West;
 41. thence southerly, a distance of approximately 0.2 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of an unimproved road, bears

- easterly and westerly, at observed latitude 40°04'26.492" North, longitude 114°45'57.034" West;
42. thence westerly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 15 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°04'33.920" North, longitude 114°46'58.091" West;
43. thence S. 15°24'10" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of the unimproved road, at observed latitude 40°04'31.920" North, longitude 114°46'58.808" West;
44. thence easterly, a distance of approximately 1.0 mile, to intersection with the north and south center line of the northwest one-quarter of section 5, T. 25 N., R. 64 E., at approximate latitude 40°04'24" North, longitude 114°45'55" West;
45. thence southerly, a distance of approximately 0.25 miles, on the north and south center line of the northwest one-quarter of section 5, T. 25 N., R. 64 E., to intersection with a line parallel with and 100 feet westerly of the westerly edge of aforementioned improved road, described in course No. 39, bears northerly and southerly, at approximate latitude 40°04'12" North, longitude 114°45'56" West;
46. thence southerly, a distance of approximately 0.25 miles, on a line parallel with and 100 feet westerly of the westerly edge of the improved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of an unimproved road, bears southwest, at observed latitude 40°04'0.030" North, longitude 114°46'0.016" West;
47. thence southwest, a distance of approximately 500 feet, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a jeep trail, bears southwest, at observed latitude 40°03'56.163" North, longitude 114°46'04.175" West;

48. thence southwesterly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of an unimproved road, bears easterly and westerly, at observed latitude 40°03'47.669" North, longitude 114°46'21.686" West;
49. thence westerly turning northwesterly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet northerly and northeasterly of the northerly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°03'50.992" North, longitude 114°47'32.416" West;
50. thence S. 39°25'20" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road, at observed latitude 40°03'49.389" North, longitude 114°47'34.131" West;
51. thence southeasterly turning easterly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet southwesterly and southerly of the southwesterly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of a second unimproved road, bears northwesterly and southeasterly, at observed latitude 40°03'44.515" North, longitude 114°46'59.728" West;
52. thence southeasterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned jeep trail, described in course No. 48, bears northeasterly and southwesterly, at observed latitude 40°03'29.873" North, longitude 114°46'40.596" West;
53. thence southwesterly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail to a stainless steel post,

- 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at the base of left bank of a wash, course easterly, at observed latitude 40°02'54.775" North, longitude 114°47'19.319" West;
54. thence westerly, a distance of approximately 0.6 miles, with the meanders of the base of left bank of the wash, course easterly to a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, cemented in a drill hole of solid rock, with top marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of an unimproved road, bears westerly and easterly, at observed latitude 40°02'59.843" North, longitude 114°48'01.540" West;
55. thence S. 0°34'50" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of the unimproved road, at observed latitude 40°02'57.768" North, longitude 114°48'01.512" West;
56. thence easterly and southeasterly, a distance of approximately 0.8 miles, on a line parallel with and 100 feet southerly and southwesterly of the southerly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned jeep trail, described in course No. 53, bears northeasterly and southwesterly, at observed latitude 40°02'30.568" North, longitude 114°47'29.405" West;
57. thence southwesterly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 40°01'20.859" North, longitude 114°47'58.472" West;
58. thence northwesterly, a distance of approximately 1.2 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°01'52.492" North, longitude 114°49'06.198" West;

59. thence S. 2°16'00" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 14 inches in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road at observed latitude 40°01'50.419" North, longitude 114°49'06.092" West;
60. thence southeasterly, a distance of approximately 1.2 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned jeep trail, described in course No. 57, bears northeasterly and southwesterly, at observed latitude 40°01'18.478" North, longitude 114°47'59.477" West;
61. thence southwesterly, a distance of approximately 1.45 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at the base of left bank of a wash, course southeasterly, at observed latitude 40°00'07.067" North, longitude 114°48'29.249" West;
62. thence northwesterly, a distance of approximately 0.3 miles, with the meanders of the base of left bank of wash, course southeasterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 40°00'13.335" North, longitude 114°48'47.245" West;
63. thence northwesterly turning westerly, a distance of approximately 0.8 miles, on a line parallel with and 100 feet northeasterly and northerly of the northeasterly and northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°00'40.992" North, longitude 114°49'25.459" West;
64. thence S. 8°37'10" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 14 inches

- in the ground over a plastic-encased magnet, to solid rock, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of the unimproved road, at observed latitude 40°00'38.941" North, longitude 114°49'25.864" West;
65. thence easterly turning southeasterly, a distance of approximately 1.2 miles, on a line parallel with and 100 feet southerly and southwesterly of the southerly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second unimproved road, bears northwesterly and southeasterly, at observed latitude 39°59'56.226" North, longitude 114°48'40.647" West;
66. thence northwesterly turning westerly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet northeasterly and northerly of the northeasterly and northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°00'02.959" North, longitude 114°49'19.694" West;
67. thence westerly, a distance of approximately 350 feet, to a point, at approximate latitude 40°00'02.35" North, longitude 114°49'24.27" West;
68. thence southerly, a distance of approximately 180 feet, to a point, at approximate latitude 40°00'00.86" North, longitude 114°49'24.33" West;
69. thence southeasterly, a distance of approximately 400 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 39°59'57.386" North, longitude 114°49'20.986" West;
70. thence southeasterly, a distance of approximately 0.15 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of a second unimproved road, bears easterly and westerly, at observed latitude 39°59'51.264" North, longitude 114°49'14.215" West;

71. thence westerly turning southwesterly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet northerly and northwesterly of the northerly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 39°59'44.853" North, longitude 114°49'50.564" West;
72. thence S. 17°30'00" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road, at observed latitude 39°59'42.874" North, longitude 114°49'49.753" West;
73. thence northeasterly, a distance of approximately 300 feet, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a second unimproved road, extending northeasterly, at approximate latitude 39°59'44.4" North, longitude 114°49'46.4" West;
74. thence northeasterly, a distance of approximately 0.25 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 39°59'48.282" North, longitude 114°49'35.328" West;
75. thence S. 23°50'20" W., a distance of 3,831.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 26 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary at observed latitude 39°59'13.658" North, longitude 114°49'55.216" West;
76. thence S. 83°31'00" W., a distance of 1,151.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary at intersection with a line parallel with and 100 feet westerly of the westerly edge of a jeep trail, bears northerly and southerly, at observed latitude 39°59'12.374" North, longitude 114°50'09.905" West;
77. thence southerly, a distance of approximately 0.85 miles, on a line parallel with and 100 feet westerly of the westerly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2

- inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of an unimproved road, bears easterly and westerly, at observed latitude 39°58'30.321" North, longitude 114°50'00.397" West;
78. thence westerly, a distance of approximately 0.35 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second unimproved road, bears northwesterly and southeasterly, at observed latitude 39°58'27.405" North, longitude 114°50'23.379" West;
79. thence northwesterly, a distance of approximately 2.7 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 39°59'37.077" North, longitude 114°52'30.065" West;
80. thence N. 28°07'20" E., a distance of 523.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 39°59'41.634" North, longitude 114°52'26.898" West;
81. thence N. 70°31'00" W., a distance of 138.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 39°59'42.091" North, longitude 114°52'28.579" West;
82. thence S. 28°10'00" W., a distance of 418.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 39°59'38.451" North, longitude 114°52'31.113" West;
83. thence S. 63°06'30" W., a distance of 244.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of aforementioned unimproved road, described in course No. 79, bears southeasterly,

at observed latitude 39°59'37.360" North, longitude 114°52'33.909" West;

84. thence southeasterly, a distance of approximately 2.8 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at the base of left bank of a wash, course easterly, at observed latitude 39°58'26.056" North, longitude 114°50'25.438" West;
85. thence westerly, a distance of approximately 0.3 miles, with the meanders of the base of left bank of a wash, course easterly, to a point on said base of left bank, at approximate latitude 39°58'26" North, longitude 114°50'46" West;
86. thence southerly, a distance of approximately 0.55 miles, to the base of left bank of a wash, course easterly, at approximate latitude 39°57'59.5" North, longitude 114°50'57.5" West;
87. thence westerly, a distance of approximately 0.15 miles, with the meanders of the base of left bank of the wash, course easterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a jeep trail, bears northerly and southeasterly, at observed latitude 39°58'00.648" North, longitude 114°51'06.814" West;
88. thence northerly, a distance of approximately 125 feet, on a line parallel with and 100 feet easterly of the easterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 39°58'01.825" North, longitude 114°51'06.727" West;
89. thence S. 80°18'00" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of the jeep trail, at observed latitude 39°58'01.476" North, longitude 114°51'09.384" West;
90. thence southerly turning southeasterly and southerly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet westerly and southwesterly of the westerly and southwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating

- the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second jeep trail, at observed latitude 39°57'49.020" North, longitude 114°51'04.740" West;
91. thence northwesterly turning southerly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet northeasterly and westerly of the northeasterly and westerly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 39°57'42.242" North, longitude 114°51'57.557" West;
 92. thence westerly, a distance of approximately 0.3 miles, to a point at approximate latitude 39°57'41.84" North, longitude 114°52'17.6" West;
 93. thence northeasterly, a distance of approximately 0.2 miles, to a spur, slopes southeasterly, at approximate latitude 39°57'50.5" North, longitude 114°52'13" West;
 94. thence northwesterly, a distance of approximately 0.2 miles, along the summit of the spur to a knoll, at approximate latitude 39°57'57" North, longitude 114°52'24" West;
 95. thence westerly, a distance of approximately 1.2 miles, along the summit of a ridge, bears easterly and westerly, to a knoll, at approximate elevation of 3,206 meters and approximate latitude 39°57'58" North, longitude 114°53'45" West;
 96. thence northwesterly, a distance of approximately 1.7 miles, continuing along the summit of the ridge to a knoll, at approximate elevation of 2,601 meters and approximate latitude 39°58'42" North, longitude 114°55'16" West;
 97. thence northwesterly, a distance of approximately 0.65 miles, to a spur, slopes southwesterly, at approximate latitude 39°59'13" North, longitude 114°55'35" West;
 98. thence northeasterly, a distance of approximately 1.0 mile, to the base of right bank of a wash, course westerly, at approximate latitude 40°00'01" North, longitude 114°55'09" West;
 99. thence westerly turning northwesterly, a distance of approximately 0.35 miles, with the meanders of the base of right bank of the wash, course westerly and northwesterly, to a point on said base of right bank, at approximate latitude 40°00'04" North, longitude 114°55'30" West;
 100. thence northeasterly, a distance of approximately 0.75 miles, to a spur, slopes westerly, at approximate latitude 40°00'32" North, longitude 114°54'56" West;

101. thence northeasterly, a distance of approximately 0.85 miles, to a point, at approximate latitude 40°01'12.95" North, longitude 114°54'33.08" West;
102. thence easterly, a distance of approximately 0.5 miles, to a point, at approximate latitude 40°01'08.55" North, longitude 114°54'00.67" West;
103. thence northeasterly, a distance of approximately 0.3 miles, to a point, at approximate latitude 40°01'21.13" North, longitude 114°53'49.13" West;
104. thence easterly, a distance of approximately 0.15 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a jeep trail, bears northeasterly and southwesterly, at observed latitude 40°01'20.821" North, longitude 114°53'37.743" West;
105. thence northerly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet easterly of the easterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line and at the centerline of a second jeep trail, bears northeasterly and southwesterly, at observed latitude 40°01'30.691" North, longitude 114°53'31.334" West;
106. thence northwesterly turning northerly, a distance of approximately 0.5 miles, continuing on the line parallel with and 100 feet northeasterly and easterly of the northeasterly and easterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude 40°01'53.215" North, longitude 114°53'39.867" West;
107. thence northeasterly, a distance of approximately 0.9 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of a jeep trail, bears easterly and westerly, at observed latitude 40°02'24.002" North, longitude 114°52'55.336" West;

108. thence easterly, a distance of approximately 450 feet, on a line parallel with and 100 feet southerly of the southerly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°02'23.016" North, longitude 114°52'49.919" West;
109. thence N. 39°02'20" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 25 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of the jeep trail, at observed latitude 40°02'24.628" North, longitude 114°52'48.219" West;
110. thence westerly turning northwesterly, a distance of approximately 550 feet, on a line parallel with and 100 feet northerly and northeasterly of the northerly and northeasterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in course No. 107, bears northerly and southerly, at observed latitude 40°02'26.852" North, longitude 114°52'53.872" West;
111. thence northerly turning northeasterly, a distance of approximately 1.4 miles, on a line parallel with and 100 feet easterly and southeasterly of the easterly and southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of a jeep trail, bears southeasterly, at observed latitude 40°03'05.506" North, longitude 114°52'15.894" West;
112. thence southeasterly, a distance of approximately 0.45 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°02'49.037" North, longitude 114°51'55.964" West;
113. thence N. 21°54'10" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge

- of the jeep trail, at observed latitude 40°02'50.962" North, longitude 114°51'54.957" West;
114. thence northwesterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned unimproved road, described in course No. 111, bears northeasterly and southwesterly, at observed latitude 40°03'06.185" North, longitude 114°52'13.133" West;
 115. thence northeasterly turning northerly and easterly, a distance of approximately 2.5 miles, on a line parallel with and 100 feet southeasterly and easterly of the southeasterly and easterly edge of the unimproved road to intersection with a line parallel with and 100 feet southerly of the southerly edge of a second unimproved road, at approximate latitude 40°04'40.5" North, longitude 114°51'16.5" West;
 116. thence easterly, a distance of approximately 0.1 mile, on a line parallel with and 100 feet southerly of the southerly edge of the unimproved road, to intersection with the line between sections 4 and 34, on the south boundary of T. 26 N., R. 63 E., (Fifth Standard Parallel North), at approximate latitude 40°04'41" North, longitude 114°51'10" West;
 117. thence easterly, a distance of approximately 0.1 mile, to the east one-sixteenth section corner of section 34 only, on the south boundary of T. 26 N., R. 63 E., (Fifth Standard Parallel North);
 118. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of the southeast one-quarter of section 34, T. 26 N., R. 63 E., to the center-east, one-sixteenth section corner of section 34;
 119. thence westerly, a distance of approximately 0.25 miles, on the east and west center line of section 34, T. 26 N., R. 63 E., to the center one-quarter of section 34;
 120. thence southerly, a distance of approximately 0.5 miles, on the north and south center line of section 34, T. 26 N., R. 63 E., to the one-quarter section corner of section 34 only, on the south boundary of the township and the intersection with a line parallel with and 100 feet westerly of the westerly edge of the aforementioned unimproved road, described in course No. 115, bears northerly and southerly, at approximate latitude 40°04'41" North, longitude 114°51'20" West;
 121. thence southerly turning southwesterly, a distance of approximately 2.4 miles, on a line parallel with and 100 feet westerly and northwesterly of the westerly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a

- plastic-encased magnet, with a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°03'16.193" North, longitude 114°52'07.785" West;
122. thence N. 37°19'20" W., a distance of 383.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 40°03'19.203" North, longitude 114°52'10.772" West;
 123. thence S. 52°44'00" W., a distance of 371.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, in a mound of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 40°03'16.980" North, longitude 114°52'14.574" West;
 124. thence S. 40°04'40" E., a distance of 716.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned unimproved road, described in course No. 121, bears northeasterly and southwesterly, at observed latitude 40°03'11.564" North, longitude 114°52'08.644" West;
 125. thence southwesterly turning southerly, a distance of approximately 1.6 miles, on a line parallel with and 100 feet northwesterly and westerly of the northwesterly and westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, with a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a second unimproved road, bearing southwesterly, at observed latitude 40°02'26.749" North, longitude 114°52'56.577" West;
 126. thence southwesterly, a distance of approximately 0.7 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°02'14.172" North, longitude 114°53'39.859" West;
 127. thence N. 53°18'10" W., a distance of 745.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude 40°02'18.571" North, longitude 114°53'47.538" West;

128. thence S. $74^{\circ}56'20''$ W., a distance of 527.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude $40^{\circ}02'17.216''$ North, longitude $114^{\circ}53'54.084''$ West;
129. thence S. $52^{\circ}26'40''$ E., a distance of 1,001.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned unimproved road, described in course No. 126, bears northeasterly and southwesterly, at observed latitude $40^{\circ}02'11.184''$ North, longitude $114^{\circ}53'43.876''$ West;
130. thence southwesterly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude $40^{\circ}02'06.481''$ North, longitude $114^{\circ}53'54.725''$ West;
131. thence N. $26^{\circ}48'20''$ W., a distance of 499.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude $40^{\circ}02'10.887''$ North, longitude $114^{\circ}53'57.621''$ West;
132. thence S. $45^{\circ}00'40''$ W., a distance of 780.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at observed latitude $40^{\circ}02'05.438''$ North, longitude $114^{\circ}54'04.712''$ West;
133. thence S. $54^{\circ}00'40''$ E., a distance of 803.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, and in a collar of stone, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, to intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned unimproved road, described in course No. 130, bears northeasterly and southwesterly, at observed latitude $40^{\circ}02'00.775''$ North, longitude $114^{\circ}53'56.359''$ West;
134. thence southwesterly, a distance of approximately 0.2 miles, on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the

- ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°01'52.554" North, longitude 114°54'01.066" West;
135. thence westerly, a distance of approximately 400 feet, to the corner of sections 13 and 24, on the east boundary of T. 25 N., R. 62 E.;
 136. thence westerly, a distance of approximately 0.5 miles, on the line between sections 13 and 24, T. 25 N., R. 62 E., to the one-quarter section corner of sections 13 and 24;
 137. thence northerly, a distance of approximately 1.0 mile, on the north and south center line of section 13, T. 25 N., R. 62 E., to the one-quarter section corner of sections 12 and 13;
 138. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of section 12, T. 25 N., R. 62 E., to the center south one-sixteenth section corner of section 12;
 139. thence northerly, a distance of approximately 0.25 miles, on the north and south center line of section 12, T. 25 N., R. 62 E., to the center one-quarter section corner of section 12;
 140. thence northerly, a distance of approximately 0.5 miles, on the north and south center line of section 12, T. 25 N., R. 62 E., to the one-quarter section corner of sections 1 and 12;
 141. thence northerly, a distance of approximately 1.0 mile, on the north and south center line of section 1, T. 25 N., R. 62 E., to the eighty center one-sixteenth section corner of section 1;
 142. thence northerly, a distance of approximately 0.2 miles, on the north and south center line of section 1, T. 25 N., R. 62 E., to the one-quarter section corner of section 1 only, on the south boundary of T. 26 N., R. 62 E., (Fifth Standard Parallel North);
 143. thence northerly, a distance of approximately 50 feet, to intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, at approximate latitude 40°04'42" North, longitude 114°54'38" West;
 144. thence easterly turning southerly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet southerly and westerly of the southerly and westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, and in a mound of stone, 3 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, on said line, at observed latitude 40°04'33.336" North, longitude 114°54'12.104" West;
 145. thence S. 71°24'50" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, and in a mound of

stone, 2 feet base, to top, with brass cap marked GCW N83921 2014 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of the unimproved road, at observed latitude 40°04'32.674" North, longitude 114°54'09.544" West;

146. thence northerly turning westerly, a distance of approximately 0.7 miles, on a line parallel with and 100 feet easterly and northerly of the easterly and northerly edge of the unimproved road, to intersection with the north and south center line of section 31, T. 26 N., R. 63 E., at approximate latitude 40°04'44" North, longitude 114°54'46" West;
147. thence northerly, a distance of approximately 0.2 miles, on the north and south center line of section 31, T. 26 N., R. 63 E., to the center south one-sixteenth section corner of section 31;
148. thence westerly, a distance of approximately 0.5 miles, on the east and west center line of the southwest one-quarter of section 31, T. 26 N., R. 63 E., to the south one-sixteenth section corner of sections 31 and 36, on the west boundary of T. 26 N., R. 63 E.;
149. thence northerly, a distance of approximately 0.75 miles, on the line between sections 31 and 36, on the west boundary of T. 26 N., R. 63 E., to the corner of sections 25, 30, 31, and 36;
150. thence northerly, a distance of approximately 0.25 miles, on the line between sections 25 and 30, on the west boundary of T. 26 N., R. 63 E., to the south one-sixteenth section corner of sections 25 and 30;
151. thence northeasterly, a distance of approximately 1.0 mile, to a spur, slopes northwesterly, at approximate latitude 40°06'34" North, longitude 114°54'45" West;
152. thence northeasterly, a distance of approximately 0.3 miles, to a point, at approximate latitude 40°06'37.62" North, longitude 114°54'25.23" West;
153. thence northwesterly, a distance of approximately 0.3 miles, to a point, at approximate latitude 40°06'47.77" North, longitude 114°54'40.28" West;
154. thence northerly, a distance of approximately 0.6 miles, to intersection with the line between sections 18 and 19, T. 26 N., R. 63 E., at approximate latitude 40°07'20" North, longitude 114°54'36" West;
155. thence easterly, a distance of approximately 0.35 miles, to the corner of sections 17, 18, 19, and 20, T. 26 N., R. 63 E.; and the Point of Beginning.

The area contained within the bounds of this description is 42,620 acres, more or less.

END OF DESCRIPTION

The acreages are based on a GIS polygon projected onto the 1983 North American Datum Universal Transverse Mercator projection, zone 11.

The direction of each line is with reference to the true meridian.

The geographic positions noted as "approximate" latitude and longitude are referenced to the North American Datum of 1983 and were digitized from the following editions of the United States Geologic Survey 7.5 minute quadrangle maps. The elevations noted are referenced to sea level and are taken from these same maps:

1. Paris Creek, Nev., Provisional Edition 1984
2. Goshute Creek, Nev., Provisional Edition 1984
3. Cherry Creek, Nev., 1965, Photo-revised 1981
4. Cherry Creek Station, Nev., 1982

The geographic positions noted as "observed" latitude and longitude are referenced to the North American Datum of 1983. Observed positions were determined in 2014 utilizing Global Positioning System (GPS), Real Time Kinematic (RTK) observations. All RTK observations were carried forward from local control established using GPS static observations processed with the National Geodetic Survey Online Positioning User Service (OPUS) referenced to the following Continuously Operating Reference Stations (CORS): "EGAN EGAN BRGN NV1996 CORS ARP", "NVPI PIOCHE CORS ARP", and "LKN1 ELKO CORS ARP", "SALMONFALLNV CORS ARP" and "SPRING VALLEY CORS ARP."

WILDERNESS AREA
Goshute Canyon Wilderness
Bureau of Land Management

I hereby certify that the maps and legal boundary description herewith represents the boundary of the Goshute Canyon Wilderness within the jurisdiction of the Ely District Office, Nevada, Bureau of Land Management.

Signed: _____ Date: _____
Chief, Branch of Geographic Sciences
Bureau of Land Management, Nevada

I hereby certify and accept the maps and legal boundary description of Goshute Canyon Wilderness within the Ely District Office, Nevada, Bureau of Land Management, as entered into the Wilderness System under the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006.

Signed: _____ Date: _____
State Director, Nevada
Bureau of Land Management