

Government Peak Wilderness
Legal Boundary Description

The boundaries of the Government Peak Wilderness established in the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006, Bureau of Land Management serial No. N-83919, is comprised of two parcels: PARCEL ONE is located in Townships 19 North, Ranges 69 and 70 East, and Township 20 North, Range 70 East, Mount Diablo Meridian. PARCEL TWO is located in Townships 19 North, Ranges 69 and 70 East, Mount Diablo Meridian. The entire wilderness, located in White Pine County, in the state of Nevada, is more particularly described as follows:

PARCEL ONE

1. BEGINNING at a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 39°30'52.799" North, longitude 114°09'45.560" West; thence northwesterly, a distance of approximately 0.4 miles, to a point, at approximate latitude 39°31'11.90" North, longitude 114°09'57.00" West;
2. thence northeasterly, a distance of approximately 1.4 miles, to a spur, slopes northwesterly, at approximate latitude 39°32'15" North, longitude 114°09'08" West;
3. thence northerly, a distance of approximately 0.3 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude 39°32'31.406" North, longitude 114°09'06.516" West;
4. thence northeasterly, a distance of approximately 0.85 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°33'06.453" North, longitude 114°08'32.899" West;
5. thence northeasterly, a distance of approximately 0.5 miles, to a spur, slopes northeasterly, at approximate latitude 39°33'15" North, longitude 114°08'00" West;
6. thence southerly, a distance of approximately 0.6 miles, to a point, at approximate latitude 39°32'43.70" North, longitude 114°07'52.70" West;

7. thence southwesterly, a distance of approximately 0.35 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°32'30.091" North, longitude 114°08'06.489" West;
8. thence N. 33°17'30" W., a distance of 1,104.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground, over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°32'39.211" North, longitude 114°08'14.224" West;
9. thence S. 37°21'00" W., a distance of 171.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°32'37.860" North, longitude 114°08'15.556" West;
10. thence S. 30°04'10" E., a distance of 1,869.4 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°32'21.775" North, longitude 114°08'03.555" West;
11. thence southerly, a distance of approximately 1.1 miles, to a point, at approximate latitude 39°31'23.75" North, longitude 114°08'12.35" West;
12. thence southerly, a distance of approximately 0.9 miles, to a point, at approximate latitude 39°30'37.65" North, longitude 114°08'08.80" West;
13. thence southwesterly, a distance of approximately 0.35 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 39°30'22.972" North, longitude 114°08'24.780" West;
14. thence northwesterly, a distance of approximately 1.55 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to the Point of Beginning.

The area contained within the bounds of PARCEL ONE of this description is 2,180 acres, more or less.

PARCEL TWO

1. BEGINNING at a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on a line parallel with and 100 feet northwesterly of the northwesterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude 39°28'44.428" North, longitude 114°09'33.855" West; thence southwesterly turning southeasterly and westerly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet northwesterly, southwesterly and northerly of the northwesterly, southwesterly and northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 39°28'41.651" North, longitude 114°09'49.463" West;
2. thence westerly turning southwesterly, a distance of approximately 0.35 miles, continuing on the line parallel with and 100 feet northerly and northwesterly of the northerly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line and at the centerline of a second unimproved road, extending northwesterly, at observed latitude 39°28'34.820" North, longitude 114°10'09.946" West;
3. thence southwesterly, a distance of approximately 0.2 miles, to a spur, slopes easterly, at approximate latitude 39°28'27" North, longitude 114°10'18" West;
4. thence westerly, a distance of approximately 1.0 mile, to a point, at approximate latitude 39°28'18.30" North, longitude 114°11'24.25" West;
5. thence northerly, a distance of approximately 0.3 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of an unimproved road, bears northerly and southwesterly, at observed latitude 39°28'33.624" North, longitude 114°11'29.037" West;
6. thence northerly turning northeasterly, a distance of approximately 0.75 miles, on a line parallel with and 100 feet easterly and southeasterly of the easterly and southeasterly edge of the unimproved road to a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, cemented in a drill hole of solid rock, marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 39°28'55.305" North, longitude 114°11'01.648" West;

7. thence N. $11^{\circ}20'30''$ E., a distance of 210.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 10 inches in the ground to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 feet base, to top, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road, at observed latitude $39^{\circ}28'57.349''$ North, longitude $114^{\circ}11'01.119''$ West;
8. thence southwesterly turning southerly, a distance of approximately 0.7 miles, on a line parallel with and 100 feet northwesterly and westerly of the northwesterly and westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 25 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line, at observed latitude $39^{\circ}28'38.809''$ North, longitude $114^{\circ}11'32.173''$ West;
9. thence southwesterly, a distance of approximately 0.55 miles, to a point, at approximate latitude $39^{\circ}28'19.90''$ North, longitude $114^{\circ}12'00.75''$ West;
10. thence northwesterly, a distance of approximately 0.4 miles, to a point, at approximate latitude $39^{\circ}28'27.10''$ North, longitude $114^{\circ}12'25.85''$ West;
11. thence northerly, a distance of approximately 0.4 miles, to a point, at approximate latitude $39^{\circ}28'46.15''$ North, longitude $114^{\circ}12'34.15''$ West;
12. thence northeasterly, a distance of approximately 0.3 miles, to a point, at approximate latitude $39^{\circ}28'57.20''$ North, longitude $114^{\circ}12'21.20''$ West;
13. thence northerly, a distance of approximately 0.75 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of an unimproved road, bears northerly and southerly, at observed latitude $39^{\circ}29'36.826''$ North, longitude $114^{\circ}12'18.622''$ West;
14. thence northerly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet easterly of the easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line, located near the terminus of road, at observed latitude $39^{\circ}29'57.914''$ North, longitude $114^{\circ}12'15.742''$ West;
15. thence N. $79^{\circ}53'50''$ E., a distance of 496.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 6 inches in the ground over a plastic-encased magnet, to solid rock, and

in a mound of stone, 4 feet base, to top, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°29'58.775" North, longitude 114°12'09.503" West;

16. thence northeasterly, a distance of approximately 0.45 miles, along the summit of a spur, slopes northeasterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 23 inches in the ground over a plastic-encased magnet, and in a mound of stone, 2 feet base, to top, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at the base of right bank of wash, course southeasterly, at observed latitude 39°30'18.264" North, longitude 114°11'51.493" West;
17. thence southeasterly turning northeasterly, a distance of approximately 0.4 miles, with the meanders of the base of right bank of the wash, to a point on said base of right bank, at approximate latitude 39°30'30" North, longitude 114°11'31" West;
18. thence northeasterly, a distance of approximately 0.35 miles, to a point on a knoll, at approximate latitude 39°30'45" North, longitude 114°11'20" West;
19. thence southeasterly, a distance of approximately 0.2 miles, to a point, at approximate latitude 39°30'38.00" North, longitude 114°11'08.10" West;
20. thence southwesterly, a distance of approximately 0.2 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at the intersection with a line parallel with and 100 feet westerly of the westerly edge of an unimproved road, bears northerly and southerly, at observed latitude 39°30'29.338" North, longitude 114°11'13.203" West;
21. thence southerly turning easterly, a distance of approximately 0.95 mile, on a line parallel with and 100 feet westerly and southerly of the westerly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 39°29'45.435" North, longitude 114°11'15.038" West;
22. thence N. 11°10'00" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of the unimproved road, at observed latitude 39°29'47.471" North, longitude 114°11'14.520" West;

23. thence northwesterly, a distance of approximately 250 feet, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 39°29'48.498" North, longitude 114°11'17.371" West;
24. thence N. 5°33'50" E., a distance of 1,573.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked GPW N83919 2013 and a line indicating the direction of the boundary, at observed latitude 39°30'03.969" North, longitude 114°11'15.426" West;
25. thence northeasterly, a distance of approximately 0.8 miles, to a point, at approximate latitude 39°30'29.20" North, longitude 114°10'33.15" West;
26. thence northeasterly, a distance of approximately 0.55 miles, to a spur, slopes northwesterly, at approximate latitude 39°30'55" North, longitude 114°10'19" West;
27. thence southeasterly, a distance of approximately 0.65 miles, to a point, at approximate latitude 39°30'41.95" North, longitude 114°09'37.80" West;
28. thence easterly, a distance of approximately 0.15 miles, to a spur, slopes northeasterly, at approximate latitude 39°30'43" North, longitude 114°09'27" West;
29. thence southerly, a distance of approximately 0.25 miles, to a point, at approximate latitude 39°30'30.55" North, longitude 114°09'26.00" West;
30. thence southeasterly, a distance of approximately 0.35 miles, to a spur, slopes northeasterly, at approximate latitude 39°30'19" North, longitude 114°09'06" West;
31. thence southerly, a distance of approximately 0.6 miles, to a spur, slopes easterly, at approximate latitude 39°29'49" North, longitude 114°08'52" West;
32. thence southerly, a distance of approximately 0.45 miles, to a point, at approximate latitude 39°29'25.90" North, longitude 114°09'00.40" West;
33. thence southwesterly, a distance of approximately 0.55 miles, to the thread of a creek, course southeasterly, at approximate latitude 39°29'05" North, longitude 114°09'24" West;
34. thence southerly, a distance of approximately 0.45 miles, to the Point of Beginning.

The area contained within the bounds of PARCEL TWO of this description is 4,140 acres, more or less.

The total area of PARCEL ONE and PARCEL TWO is 6,320 acres, more or less.

END OF DESCRIPTION

The acreages are based on a GIS polygon projected onto the 1983 North American Datum Universal Transverse Mercator projection, zone 11.

The direction of each line is with reference to the true meridian.

The geographic positions noted as "approximate" latitude and longitude are referenced to the North American Datum of 1983 and were digitized from the following editions of the United States Geologic Survey 7.5 minute quadrangle maps:

Government Peak, Nev., 1986
Mormon Jack Pass, Nev., 1986

The geographic positions noted as "observed" latitude and longitude are referenced to the North American Datum of 1983. Observed positions were determined in 2013 utilizing Global Positioning System (GPS), carrier phase differential methods. Real Time Kinematic (RTK) techniques were utilized to carry forward positions determined with Static observations processed using the National Geodetic Survey Online Positioning User Service (OPUS), which referenced the following Continuously Operating Reference Stations (CORS):

"EGAN BRGN NV1996 ARP"
"KNOLLSWESWT UT 2006 ARP"
"SPRING VALLEY BRGN NV1999 ARP"
"ELKO ARP"
"GOSH BRGN UT1996 ARP"
"DELTAMUNI UT2004 ARP"
"PIOCHE ARP"

WILDERNESS AREA
Government Peak Wilderness
Bureau of Land Management

I hereby certify that the map and legal boundary description herewith represents the boundary of the Government Peak Wilderness within the jurisdiction of the Ely District Office, Nevada, Bureau of Land Management.

Signed: _____ Date: _____
Chief, Branch of Geographic Sciences
Bureau of Land Management, Nevada

I hereby certify and accept the map and legal boundary description of Government Peak Wilderness within the Ely District Office, Nevada, Bureau of Land Management, as entered into the Wilderness Area System and included in the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006.

Signed: _____ Date: _____
State Director, Nevada
Bureau of Land Management