

Highland Ridge Wilderness
Legal Boundary Description

The boundary of the Highland Ridge Wilderness established in the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006, Bureau of Land Management serial No. N-83918, located in Township 9 1/2 North, Range 70 East, Townships 10 North, Ranges 68, 69, and 70 East, Townships 11 North, Ranges 68, 69, and 70 East, and Township 12 North, Range 68 East, Mount Diablo Meridian, White Pine County, in the state of Nevada, is more particularly described as follows:

1. BEGINNING at the corner of sections 18 and 19 only, on the west boundary of T. 11 N., R. 69 E.; thence easterly, a distance of approximately 4.0 miles, on the lines between sections 18 and 19, sections 17 and 20, sections 16 and 21, and sections 15 and 22, T. 11 N., R. 69 E., to the corner of sections 14, 15, 22, and 23;
2. thence northerly, a distance of approximately 0.55 miles, on the line between sections 14 and 15, T. 11 N., R. 69 E., at approximate latitude 38°49'35.6" North, longitude 114°12'24" West;
3. thence easterly, a distance of approximately 0.45 miles, to the base of right bank of a wash, course northerly, at approximate latitude 38°49'35.6" North, longitude 114°11'53" West;
4. thence northerly, a distance of approximately 0.75 miles, with the meanders of the base of right bank of the wash, course northerly, to a point on said base of right bank, at approximate latitude 38°50'12.5" North, longitude 114°11'42" West;
5. thence northeasterly, a distance of approximately 0.3 miles, to a point, at approximate latitude 38°50'25" North, longitude 114°11'33" West;
6. thence northerly, a distance of approximately 0.1 mile, to a point, at approximate latitude 38°50'30.5" North, longitude 114°11'32.0" West;
7. thence northeasterly, a distance of approximately 0.1 mile, to intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a trailhead vehicle parking area, at approximate latitude 38°50'33.50" North, longitude 114°11'26.85" West;
8. thence southeasterly turning northeasterly, a distance of approximately 250 feet, on a line parallel with and 100 feet southwesterly and southeasterly of the southwesterly and southeasterly edge of the vehicle parking area to intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at approximate latitude 38°50'34.8" North, longitude 114°11'23.8" West;
9. thence northeasterly, a distance of approximately 2.0 miles, on a line parallel with and 100 feet southeasterly of the

- southeasterly edge of the unimproved road to intersection with the line between corners No. 4 and No. 5 of Homestead Entry Survey No. 155, T. 11 N., R. 70 E., at approximate latitude 38°51'24" North, longitude 114°09'40" West;
10. thence easterly, a distance of approximately 0.15 miles, on the line between corners No. 4 and No. 5 of Homestead Entry Survey No. 155, T. 11 N., R. 70 E., to corner No. 4;
 11. thence easterly, a distance of approximately 0.35 miles, on the line between corners No. 4 and No. 3 of Homestead Entry Survey No. 155, T. 11 N., R. 70 E., to corner No. 3;
 12. thence easterly, a distance of approximately 0.45 miles, on the line between corners No. 3 and No. 2 of Homestead Entry Survey No. 155, T. 11 N., R. 70 E., to corner No. 2, identical with corner No. 5 of Homestead Entry Survey No. 184;
 13. thence easterly, a distance of approximately 0.85 miles, on the line between corners No. 5 and No. 4 of Homestead Entry Survey No. 184, to corner No. 4;
 14. thence easterly, a distance of approximately 0.15 miles, on the line between corners No. 4 and No. 3 of Homestead Entry Survey No. 184, T. 11 N., R. 70 E., to corner No. 3;
 15. thence northerly, a distance of approximately 30 feet, on the line between corners No. 3 and No. 2 of Homestead Entry Survey No. 184, T. 11 N., R. 70 E., to intersection with a line parallel with and 100 feet southerly of the southerly edge of an unimproved road, bears easterly and westerly, at approximate latitude 38°51'27" North, longitude 114°07'32" West;
 16. thence easterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet southerly of the southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of a jeep trail, bears northerly and southerly, at observed latitude 38°51'24.487" North, longitude 114°07'04.403" West;
 17. thence southerly turning southeasterly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet westerly of the westerly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second jeep trail, bears easterly and southwesterly, at observed latitude 38°51'08.301" North, longitude 114°06'54.674" West;
 18. thence southwesterly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet westerly of the westerly edge of the jeep trail to a stainless steel post, 28 inches long,

- 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°50'24.391" North, longitude 114°07'26.709" West;
19. thence southwesterly, a distance of approximately 0.55 miles, to a spur, slopes easterly, at approximate latitude 38°50'03" North, longitude 114°07'51" West;
 20. thence southerly, a distance of approximately 0.85 miles, to the base of left bank of wash, course southeasterly, at approximate latitude 38°49'18" North, longitude 114°08'06" West;
 21. thence northwesterly, a distance of approximately 0.45 miles, with the meanders of the base of the left bank of wash, course southeasterly, to a point on said base of left bank, at approximate latitude 38°49'28" North, longitude 114°08'32.5" West;
 22. thence southwesterly, a distance of approximately 0.85 miles, to a point, at approximate latitude 38°48'48.45" North, longitude 114°08'59.20" West;
 23. thence southeasterly, a distance of approximately 0.6 miles, to intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of an unimproved road, bears northeasterly and southwesterly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°48'19.492" North, longitude 114°08'44.347" West;
 24. thence southwesterly turning southerly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet northwesterly and westerly of the northwesterly and westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of a jeep trail, bears northeasterly and southwesterly, at observed latitude 38°48'11.239" North, longitude 114°08'57.814" West;
 25. thence southwesterly turning northwesterly and southwesterly, a distance of approximately 1.7 miles, on a line parallel with and 100 feet northwesterly, northeasterly and northwesterly of the northwesterly, northeasterly and northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°48'07.076" North, longitude 114°10'29.262" West;

26. thence S. $47^{\circ}36'30''$ E., a distance of 210.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the jeep trail, at observed latitude $38^{\circ}48'05.671''$ North, longitude $114^{\circ}10'27.295''$ West;
27. thence northeasterly turning southeasterly and northeasterly, a distance of approximately 1.7 miles, on a line parallel with and 100 feet southeasterly, southwesterly and southeasterly of the southeasterly, southwesterly and southeasterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the aforementioned unimproved road, described in course No. 24, bears northeasterly and southwesterly, at observed latitude $38^{\circ}48'10.792''$ North, longitude $114^{\circ}08'55.168''$ West;
28. thence northeasterly turning southeasterly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet southeasterly and southwesterly of the southeasterly and southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude $38^{\circ}47'50.745''$ North, longitude $114^{\circ}07'49.240''$ West;
29. thence southwesterly, a distance of approximately 1.7 miles, to the closing corner of sections 4 and 5, T. 10 N., R. 70 E., on the south boundary of T. 11 N., R. 70 E.;
30. thence southerly, a distance of approximately 4.0 miles, on the lines between sections 4 and 5, sections 8 and 9, sections 16 and 17, and sections 20 and 21, T. 10 N., R. 70 E., to the corner of sections 20, 21, 28, and 29;
31. thence southwesterly, a distance of approximately 1.0 mile, to a point, at approximate latitude $38^{\circ}42'13.35''$ North, longitude $114^{\circ}08'56.30''$ West;
32. thence southerly, a distance of approximately 1.2 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude $38^{\circ}41'12.817''$ North, longitude $114^{\circ}09'08.589''$ West;

33. thence northwesterly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°41'30.326" North, longitude 114°09'39.233" West;
34. thence southwesterly, a distance of approximately 0.75 miles, to a point, at approximate latitude 38°41'16.60" North, longitude 114°10'26.75" West;
35. thence westerly, a distance of approximately 0.75 miles, to a point, at approximate latitude 38°41'21.20" North, longitude 114°11'16.85" West;
36. thence northwesterly, a distance of approximately 0.35 miles, to a point at approximate latitude 38°41'34.20" North, longitude 114°11'31.80" West;
37. thence westerly, a distance of approximately 0.5 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 38°41'28.545" North, longitude 114°12'04.931" West;
38. thence northwesterly turning westerly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet northeasterly and northerly of the northeasterly and northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°41'30.672" North, longitude 114°12'21.200" West;
39. thence westerly, a distance of approximately 0.65 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of an unimproved road, in Big Spring Wash, bears northwesterly and southeasterly, at observed latitude 38°41'28.519" North, longitude 114°13'05.150" West;
40. thence northwesterly turning northerly, a distance of approximately 6.0 miles, on a line parallel with and 100 feet northeasterly and easterly of the northeasterly and easterly edge of the unimproved road in Big Spring Wash to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW

- N83918 2013 and a line indicating the direction of the boundary, on said line, near the junction with a second unimproved road, extending northwesterly in Decathon Canyon, at observed latitude 38°46'08.950" North, longitude 114°14'31.257" West;
41. thence northeasterly turning northerly, a distance of approximately 1.9 miles, continuing on the line parallel with and 100 feet southeasterly and easterly of the southeasterly and easterly edge of the unimproved road in Big Spring Wash to a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, cemented in a drill hole in solid rock, with top marked HRW N83918 2013 and a line indicating the direction of the boundary at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a second unimproved road, bears northeasterly and southwesterly, at observed latitude 38°47'34.960" North, longitude 114°13'35.320" West;
 42. thence northeasterly, a distance of approximately 0.35 miles on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°47'48.779" North, longitude 114°13'22.549" West;
 43. thence N. 42°44'10" W., a distance of 210.0 feet, to a brass tablet, 3 1/4 inch diameter, 3 1/2 inch stem, cemented in a drill hole of solid rock, with top marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road, at observed latitude 38°47'50.303" North, longitude 114°13'24.349" West;
 44. thence southwesterly, a distance of approximately 0.3 miles on a line parallel with and 100 feet northwesterly of the northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in course No. 41, bears northerly and southerly, at observed latitude 38°47'38.488" North, longitude 114°13'35.963" West;
 45. thence northerly, a distance of approximately 1.7 miles, on a line parallel with and 100 feet easterly of the easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°49'01.752" North, longitude 114°13'46.327" West;
 46. thence S. 79°59'50" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set

- 20 inches in the ground over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of the unimproved road, at observed latitude 38°49'01.217" North, longitude 114°13'48.879" West;
47. thence southerly turning southwesterly, a distance of approximately 3.6 miles, on a line parallel with and 100 feet westerly and northwesterly of the westerly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of a second unimproved road, extending westerly, at observed latitude 38°46'14.032" North, longitude 114°14'30.842" West;
48. thence westerly, a distance of approximately 300 feet, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northeasterly of the northeasterly edge of a second unimproved road, in Decathon Canyon, bears northwesterly and southeasterly, at observed latitude 38°46'13.548" North, longitude 114°14'34.369" West;
49. thence northwesterly, a distance of approximately 3.8 miles, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°48'48.364" North, longitude 114°16'45.399" West;
50. thence S. 55°13'50" W., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road, at observed latitude 38°48'47.181" North, longitude 114°16'47.577" West;
51. thence southeasterly, a distance of approximately 3.9 miles, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of aforementioned unimproved road, described

- in course No. 40, bears northeasterly and southerly, at observed latitude 38°46'08.447" North, longitude 114°14'33.856" West;
52. thence southerly, a distance of approximately 2.6 miles, on a line parallel with and 100 feet westerly of the westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of a second unimproved road extending southwesterly in West Fork Canyon, at observed latitude 38°43'58.787" North, longitude 114°14'46.159" West;
53. thence southwesterly turning northwesterly, a distance of approximately 0.3 miles, on a line parallel with and 100 feet northwesterly and northeasterly of the northwesterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of a second unimproved road, bears northerly and southerly, at observed latitude 38°44'02.876" North, longitude 114°15'01.076" West;
54. thence northerly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet easterly of the easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°44'33.111" North, longitude 114°15'08.996" West;
55. thence N. 84°28'10" W., a distance of 210.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of the unimproved road, at observed latitude 38°44'33.312" North, longitude 114°15'11.644" West;
56. thence southerly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet westerly of the westerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 6 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 4 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northwesterly of the northwesterly edge of aforementioned unimproved road, described in course No. 53, bears southeasterly and southwesterly, at observed latitude 38°44'03.588" North, longitude 114°15'04.649" West;

57. thence southwesterly turning northwesterly, a distance of approximately 4.7 miles, on a line parallel with and 100 feet northwesterly and northeasterly of the northwesterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of a second unimproved road, bears northerly and southerly, at observed latitude 38°41'25.921" North, longitude 114°18'14.731" West;
58. thence northerly turning northwesterly and northerly, a distance of approximately 2.1 miles, on a line parallel with and 100 feet easterly and northeasterly of the easterly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°42'38.436" North, longitude 114°19'38.315" West;
59. thence N. 48°16'40" E., a distance of 154.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 15 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°42'39.454" North, longitude 114°19'36.857" West;
60. thence N. 24°51'30" W., a distance of 203.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 12 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°42'41.280" North, longitude 114°19'37.937" West;
61. thence N. 86°01'00" W., a distance of 113.4 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in course No. 58, bears northwesterly and southerly, at observed latitude 38°42'41.358" North, longitude 114°19'39.363" West;
62. thence northwesterly, a distance of approximately 1.0 mile, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of a second unimproved road, bears northerly

and southerly, at observed latitude 38°43'14.927" North,
longitude 114°20'26.174" West;

63. thence northerly turning northeasterly, a distance of approximately 1.0 mile, on a line parallel with and 100 feet easterly and southeasterly of the easterly and southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°44'02.057" North, longitude 114°20'09.915" West;
64. thence S. 33°33'40" E., a distance of 143.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°44'00.879" North, longitude 114°20'08.918" West;
65. thence S. 70°37'10" E., a distance of 251.8 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southwesterly of the southwesterly edge of an unimproved road, bears northwesterly and southeasterly, at observed latitude 38°44'00.053" North, longitude 114°20'05.920" West;
66. thence southeasterly turning easterly, a distance of approximately 0.1 mile, on a line parallel with and 100 feet southeasterly and southerly of the southeasterly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°43'58.345" North, longitude 114°19'58.008" West;
67. thence N. 5°03'40" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of the unimproved road, at observed latitude 38°44'00.411" North, longitude 114°19'57.775" West;
68. thence westerly turning northwesterly, a distance of 0.15 mile, on a line parallel with and 100 feet northerly and northeasterly of the northerly and northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly

- edge of aforementioned unimproved road, described in course No. 63, bears northeasterly and southwesterly, at observed latitude 38°44'02.935" North, longitude 114°20'06.764" West;
69. thence northeasterly, a distance of approximately 2.1 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southerly of the southerly edge of a second unimproved road, bears easterly, at observed latitude 38°45'14.922" North, longitude 114°18'34.093" West;
70. thence southeasterly, a distance of approximately 175 feet, on a line parallel with and 100 feet southwesterly of the southwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°45'13.892" North, longitude 114°18'32.445" West;
71. thence N. 43°47'00" E., a distance of 210.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, to intersection with a line parallel with and 100 feet northerly of the northerly edge of the unimproved road, at observed latitude 38°45'15.391" North, longitude 114°18'30.610" West;
72. thence northwesterly, a distance of approximately 300 feet, on a line parallel with and 100 feet northeasterly of the northeasterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground over a plastic-encased magnet, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in course No. 69, bears northerly and southerly, at observed latitude 38°45'16.950" North, longitude 114°18'33.698" West;
73. thence northerly, a distance of approximately 1.5 miles on a line parallel with and 100 feet easterly of the easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 12 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 4 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°46'25.540" North, longitude 114°18'11.406" West;
74. thence N. 88°29'50" E., a distance of 55.3 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches

- in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°46'25.555" North, longitude 114°18'10.709" West;
75. thence N. 39°59'10" E., a distance of 136.6 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°46'26.589" North, longitude 114°18'09.601" West;
76. thence N. 14°04'20" W., a distance of 65.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in course No. 73, bears northerly and southerly, at observed latitude 38°46'27.213" North, longitude 114°18'09.801" West;
77. thence northeasterly turning easterly, a distance of approximately 1.1 miles, on a line parallel with and 100 feet southeasterly and southerly of the southeasterly and southerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet westerly of the westerly edge of a jeep trail, bears northerly and southerly, at observed latitude 38°47'13.301" North, longitude 114°17'44.680" West;
78. thence southerly turning southwesterly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet westerly and northwesterly of the westerly and northwesterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°46'46.373" North, longitude 114°17'39.436" West;
79. thence S. 50°16'50" E., a distance of 210.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 10 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of the jeep trail, at observed latitude 38°46'45.048" North, longitude 114°17'37.399" West;
80. thence northeasterly turning northerly, a distance of approximately 0.6 miles, on a line parallel with and 100 feet southeasterly and easterly of the southeasterly and easterly edge of the jeep trail to a stainless steel post, 28 inches long,

- 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of aforementioned unimproved road, described in course No. 77, bears northeasterly and westerly, at observed latitude 38°47'14.098" North, longitude 114°17'42.176" West;
81. thence northeasterly turning northerly, a distance of approximately 0.45 miles, on a line parallel with and 100 feet southeasterly and easterly of the southeasterly and easterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°47'32.461" North, longitude 114°17'29.828" West;
82. thence N. 58°43'10" E., a distance of 78.7 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°47'32.864" North, longitude 114°17'28.980" West;
83. thence N. 22°40'40" E., a distance of 121.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°47'33.972" North, longitude 114°17'28.388" West;
84. thence N. 47°13'40" W., a distance of 140.0 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of aforementioned unimproved road, described in course No. 81, bears northerly and southerly, at observed latitude 38°47'34.911" North, longitude 114°17'29.686" West;
85. thence northerly, a distance of approximately 2.0 miles, on a line parallel with and 100 feet easterly of the easterly edge of unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°49'11.316" North, longitude 114°17'40.334" West;
86. thence S. 58°14'20" W., a distance of 210.1 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground, over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet

- westerly of the westerly edge of the unimproved road, at observed latitude 38°49'10.223" North, longitude 114°17'42.592" West;
87. thence southerly turning southwesterly, a distance of approximately 7.6 miles, on a line parallel with and 100 feet westerly and northwesterly of the westerly and northwesterly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°44'00.477" North, longitude 114°20'24.450" West;
 88. thence northwesterly, a distance of approximately 1.2 miles, to a point, at approximate latitude 38°44'51.00" North, longitude 114°21'11.00" West;
 89. thence northerly, a distance of approximately 1.55 miles, to a point, at approximate latitude 38°46'09.00" North, longitude 114°21'39.50" West;
 90. thence northerly, a distance of approximately 1.3 miles, to the base of left bank of wash, course westerly, at approximate latitude 38°47'17" North, longitude 114°21'53" West;
 91. thence easterly, a distance of approximately 0.55 miles, with the meanders of left bank of wash, course westerly, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said base of left bank, at observed latitude 38°47'13.544" North, longitude 114°21'19.662" West;
 92. thence S. 43°40'20" E., a distance of 494.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 18 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°47'10.009" North, longitude 114°21'15.350" West;
 93. thence N. 58°06'50" E., a distance of 530.9 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground, over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at observed latitude 38°47'12.781" North, longitude 114°21'09.657" West;
 94. thence N. 19°05'30" W., a distance of 346.2 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground, over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of an unimproved road, bears northeasterly and southwesterly, at observed latitude 38°47'16.014" North, longitude 114°21'11.087" West;

95. thence northeasterly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground, over a plastic-encased magnet, in a mound of stone, 2 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with the base of left bank of a wash, course southwesterly, at observed latitude 38°47'27.225" North, longitude 114°20'43.866" West;
96. thence northeasterly, a distance of approximately 0.4 miles, with the meanders of the base of left bank of wash, course southwesterly, to a point on said base of left bank, at approximate latitude 38°47'34" North, longitude 114°20'20" West;
97. thence northwesterly, a distance of approximately 0.3 miles, to a spur, slopes southwesterly, at approximate latitude 38°47'47" North, longitude 114°20'31" West;
98. thence northwesterly, a distance of approximately 0.35 miles, to a knoll, at approximate elevation of 7,282 feet and approximate latitude 38°48'04" North, longitude 114°20'36" West;
99. thence northwesterly, a distance of approximately 0.15 miles, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 10 inches in the ground over a plastic-encased magnet to solid rock, in a mound of stone, 4 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet southeasterly of the southeasterly edge of a jeep trail, bears northeasterly and southwesterly, at observed latitude 38°48'08.851" North, longitude 114°20'45.404" West;
100. thence northeasterly, a distance of approximately 400 feet, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the jeep trail to intersection with a line parallel with and 100 feet southerly of the southerly edge of a second jeep trail, bears easterly and westerly, at approximate latitude 38°48'12.0" North, longitude 114°20'42.5" West;
101. thence easterly turning northerly and northwesterly, a distance of approximately 0.5 miles, on a line parallel with and 100 feet southerly, easterly, and northeasterly of the southerly, easterly, and northeasterly edge of the jeep trail, to intersection with the line between corners No. 3 and No. 4 of Everit No. 3 lode, Mineral Survey No. 4487, at approximate latitude 38°48'18" North, longitude 114°20'24" West;
102. thence northerly, a distance of approximately 250 feet, on the line between corners No. 3 and No. 4 of Everit No. 3 lode, Mineral Survey No. 4487, to corner No. 4;
103. thence westerly, a distance of approximately 450 feet, on the line between corners No. 4 and No. 1 of Everit No. 3 lode, Mineral Survey No. 4487, to a point on said line;

104. thence northwesterly, a distance of approximately 300 feet, to a spur, slopes southwesterly, at approximate latitude 38°48'22" North, longitude 114°20'32" West;
105. thence northeasterly, a distance of approximately 0.4 miles, to a spur, slopes westerly, at approximate latitude 38°48'41" North, longitude 114°20'20" West;
106. thence northerly, a distance of approximately 0.1 mile, to a spur, slopes southerly, at approximate latitude 38°48'47" North, longitude 114°20'20" West;
107. thence northwesterly, a distance of approximately 0.15 miles, to a point, at approximate latitude 38°48'52.35" North, longitude 114°20'28.15" West;
108. thence westerly, a distance of approximately 300 feet, to a point, at approximate latitude 38°48'52.50" North, longitude 114°20'32.00" West;
109. thence southerly, a distance of approximately 300 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet northerly of the northerly edge of an unimproved road, bears easterly and westerly, at observed latitude 38°48'49.335" North, longitude 114°20'31.454" West;
110. thence westerly, a distance of approximately 0.4 miles, on a line parallel with and 100 feet northerly of the northerly edge of the unimproved road to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 22 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°48'46.034" North, longitude 114°20'57.445" West;
111. thence N. 23°39'00" E., a distance of 1,202.5 feet, to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 24 inches in the ground, over a plastic-encased magnet, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, at intersection with a line parallel with and 100 feet easterly of the easterly edge of a jeep trail, bears northerly and southwesterly, at observed latitude 38°48'56.916" North, longitude 114°20'51.353" West;
112. thence northeasterly, a distance of approximately 3.0 miles, on a line parallel with and 100 feet southeasterly of the southeasterly edge of the jeep trail to a stainless steel post, 28 inches long, 2 1/2 inches diameter, set 20 inches in the ground over a plastic-encased magnet, in a mound of stone, 3 feet base, to top, with brass cap marked HRW N83918 2013 and a line indicating the direction of the boundary, on said line, at observed latitude 38°50'25.713" North, longitude 114°19'31.938" West;

113. thence northwesterly, a distance of approximately 0.1 mile, to the base of left bank of a wash, course southwesterly, at approximate latitude 38°50'31" North, longitude 114°19'35.5" West;
114. thence northeasterly, a distance of approximately 0.25 miles, with the meanders of the base of left bank of the wash, to a point on said left bank, at approximate latitude 38°50'34" North, longitude 114°19'21" West;
115. thence northwesterly, a distance of approximately 0.95 miles, to a point, at approximate latitude 38°51'20.10" North, longitude 114°19'46.30" West;
116. thence northwesterly, a distance of approximately 0.6 miles, to a spur, slopes westerly, at approximate latitude 38°51'40" North, longitude 114°20'18" West;
117. thence northeasterly, a distance of approximately 0.55 miles, to the base of right bank of a wash, course westerly, at approximate latitude 38°52'02" North, longitude 114°19'54.5" West;
118. thence westerly turning southwesterly, a distance of approximately 0.3 miles, with the meanders of the base of right bank of wash, course westerly and southwesterly, to a point on said right bank, at approximate latitude 38°52'00" North, longitude 114°20'14" West;
119. thence northwesterly, a distance of approximately 0.2 miles, to a spur, slopes westerly, at approximate latitude 38°52'06" North, longitude 114°20'18" West;
120. thence northeasterly, a distance of approximately 0.3 miles, to a point, at approximate latitude 38°52'14.75" North, longitude 114°20'00.20" West;
121. thence northeasterly, a distance of approximately 0.8 miles, to the one-quarter section corner of sections 22 and 27, T. 12 N., R. 68 E.;
122. thence easterly, a distance of approximately 0.5 miles, on the line between sections 22 and 27, T. 12 N., R. 68 E., to the corner of sections 22, 23, 26, and 27;
123. thence southeasterly, a distance of approximately 1.41 miles, on the diagonal line established in the traverse survey by the Bureau of Land Management, in 1987, as shown on the plat accepted May 23, 1988, to the corner of sections 25, 26, 35, and 36, T. 12 N., R. 68 E.;
124. thence southeasterly, a distance of approximately 1.05 miles, on the diagonal line established in the traverse survey by the Bureau of Land Management, in 1987, as shown on the plat accepted May 23, 1988, to the Angle Point, in section 36, T. 12 N., R. 68 E.;

125. thence southwesterly, a distance of approximately 0.29 miles, on the line established in the traverse survey by the Bureau of Land Management, in 1987, as shown on the plat accepted May 23, 1988, to the Witness Point on the line between sections 1 and 36, on the south boundary of T. 12 N., R. 68 E.;
126. thence southerly, a distance of approximately 0.42 miles, on the line established in the traverse survey by the Bureau of Land Management, in 1988, as shown on the official plat of survey, dated June 15, 1989, to Angle Point No. 4, in section 1, T. 11 N., R. 68 E.;
127. thence southwesterly, a distance of approximately 0.17 miles, on the line established in the traverse survey by the Bureau of Land Management, in 1988, as shown on the official plat of survey, dated June 15, 1989, to Angle Point No. 3, in section 1, T. 11 N., R. 68 E.;
128. thence southwesterly, a distance of approximately 380 feet, on the line established in the traverse survey by the Bureau of Land Management, in 1988, as shown on the official plat of survey, dated June 15, 1989, to Angle Point No. 2, in section 1, T. 11 N., R. 68 E.,
129. thence southerly, a distance of approximately 0.24 miles, on the line, established in the traverse survey by the Bureau of Land Management, in 1988, as shown on the official plat of survey, dated June 15, 1989, to Angle Point No. 1, in section 1, T. 11 N., R. 68 E.;
130. thence southerly, a distance of approximately 0.16 miles, on a line, established in the traverse survey by the Bureau of Land Management, in 1988, as shown on the official plat of survey, dated June 15, 1989, to the Witness Point on the line between sections 1 and 12, T. 11 N., R. 68 E.;
131. thence easterly, a distance of approximately 0.4 miles, on the line between sections 1 and 12, T. 11 N., R. 68 E., to the corner of sections 1 and 12 only, on the west boundary of T. 11 N., R. 69 E.;
132. thence southerly, a distance of approximately 1.35 miles, on the west boundary of T. 11 N., R. 69 E., to the corner of sections 18 and 19 only, on the west boundary of T. 11 N., R. 69 E., and the Point of Beginning.

The area contained within the bounds of this description is 68,560 acres, more or less.

END OF DESCRIPTION

The acreage noted in the description is based on a GIS polygon projected onto the 1983 North American Datum Universal Transverse Mercator projection, zone 11.

The direction of each line is with reference to the true meridian.

The geographic positions noted as "approximate" latitude and longitude are referenced to the North American Datum of 1983 and were digitized from the following editions of the United States Geologic Survey 7.5 minute quadrangle maps. The elevations noted are referenced to sea level and are taken from these same maps:

1. Wheeler Peak, Nev., Provisional Edition 1990
2. Minerva Canyon, Nev., Provisional Edition 1987
3. Arch Canyon, Nev., Provisional Edition 1987
4. Needle Point Spring, Nev., Provisional Edition 1987
5. Red Ledges, Nev., 1973
6. Big Springs, Nev., 1972

The geographic positions noted as "observed" latitude and longitude are referenced to the North American datum of 1983. Observed positions were determined in 2012 and 2013 utilizing Global Positioning System (GPS), Real Time Kinematic (RTK) observations. All RTK observations were carried forward from local control established using GPS static observations processed with the National Geodetic Survey Online Position User Service (OPUS) referenced to the following Continuously Operating Reference Stations (CORS): "EGAN EGAN BRGN NV1996 CORS ARP", "P105 DELTAMUNI UT2004CORS ARP; "P009 MARYSVALE UT2006", "NVPI PIOCHE CORS ARP", "LKN1 ELKO CORS ARP, "P113 KNOLLSWEST UT2006 CORS ARP", and "SPRING VALLEY CORS ARP."

WILDERNESS AREA
Highland Ridge Wilderness
Bureau of Land Management

I hereby certify that the maps and legal boundary description herewith represents the boundary of the Highland Ridge Wilderness within the jurisdiction of the Ely District Office, Nevada, Bureau of Land Management.

Signed: _____ Date: _____
Chief, Branch of Geographic Sciences
Bureau of Land Management, Nevada

I hereby certify and accept the maps and legal boundary description of Highland Ridge Wilderness within the Ely District Office, Nevada, Bureau of Land Management, as entered into the Wilderness System under the "White Pine County Conservation, Recreation, and Development Act of 2006", Public Law No. 109-432, dated December 20, 2006.

Signed: _____ Date: _____
State Director, Nevada
Bureau of Land Management